

## SAFETY DATA SHEET

## SNABBRENT YTDESINFEKTION

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Trade name

SNABBRENT YTDESINFEKTION

## Product no.

TP55750

## Unique formula identifier (UFI)

YN08-3QQQ-MCOR-1XUH

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture

Overfladedesinfektionsmiddel PT 2

Ethanol: 736 g/kg, propan-2-ol: 64 g/kg

## Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**TINGSTAD PAPPER AB**

Box 13013

S-415 02 Göteborg

Sverige

+46 31 707 20 00

<http://www.tingstad.com/>

## Contact person

Tingstad Papper AB, Kvalité och Miljö

## E-mail

kontakt@tingstad.se

## Revision

11/03/2026

## SDS Version

1.0

## Date of previous version

11/03/2026 (1.0)

## 1.4. Emergency telephone number

In urgent situations: Call 112 and request the poison information centre. (24h service)

In less severe situations: Call 010-456 6700 (24h service)

See also section 4 "First aid measures".

## SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

## 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Eye Irrit. 2; H319, Causes serious eye irritation.

## 2.2. Label elements

### Hazard pictogram(s)



### Signal word

Danger

### Hazard statement(s)

Highly flammable liquid and vapour. (H225)

Causes serious eye irritation. (H319)

### Precautionary statement(s)

#### General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

#### Prevention

Wash hands thoroughly after handling. (P264)

Wear eye protection. (P280)

#### Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. (P305+P351+P338)

If eye irritation persists: Get medical advice/attention. (P337+P313)

#### Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

#### Disposal

Dispose of contents/container in accordance with local regulation. (P501)

### Hazardous substances

Does not contain any substances required to report

### ▼ Additional labelling

Active substance(s):

propan-2-ol (14.2 g/100g)

UFI: YN08-3QQQ-MC0R-1XUH

## 2.3. Other hazards

### Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the

criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH:	40-60%	Flam. Liq. 2, H225	

	Index No.: 603-002-00-5		
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: 01-2119457558-25 Index No.: 603-117-00-0	10-15%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

## Other information

-

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

#### Eye contact

IF IN EYES: Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing for 5 minutes. Call a POISON CENTRE or a doctor.

#### Ingestion

IF SWALLOWED: Rinse mouth. Give something to drink, if exposed person is able to swallow. Do NOT induce vomiting. Call a POISON CENTRE or a doctor.

#### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure. Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 112, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Take action to prevent static discharges. Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage conditions

Room temperature 18 to 23°C

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

ethanol

Short term exposure limit (15 minutes) (ppm): 1000  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1900  
 Long term exposure limit (8 hours) (ppm): 500  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1000

Annotations:

V = Indicative short term limit.

propan-2-ol

Short term exposure limit (15 minutes) (ppm): 250  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 600  
 Long term exposure limit (8 hours) (ppm): 150  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 350

Annotations:

V = Indicative short term limit.

The Swedish Work Environment Authority's regulations and general guideline (AFS 2023:14) on limit values for respiratory exposure in the work environment.

#### DNEL

ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	343 mg/kg kropsvægt/dag
Long term – Systemic effects - Workers	Inhalation	950 mg/m <sup>3</sup>

propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	500 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

## PNEC

ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		2,75 mg/l
Soil		0,63 mg/kg dwt

propan-2-ol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Sewage treatment plant		2251 mg/L
Soil		28 mg/kg
Water		140.9 mg/L

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

No specific requirements.

### Skin protection

No specific requirements.

### Hand protection

No specific requirements.

### Eye protection

Type	Standards
Safety glasses	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Clear

#### Odour / Odour threshold

Alcohol odor

#### pH

5-6

#### Density (g/cm<sup>3</sup>)

0.87

#### Kinematic viscosity

No data available.

#### Particle characteristics

Does not apply to liquids.

#### Phase changes

##### Melting point/Freezing point (°C)

No data available.

##### Softening point/range (°C)

Does not apply to liquids.

##### Boiling point (°C)

No data available.

##### Vapour pressure

No data available.

##### Relative vapour density

No data available.

##### Decomposition temperature (°C)

No data available.

#### Data on fire and explosion hazards

##### Flash point (°C)

No data available.

##### Flammability (°C)

The material is ignitable.

##### Auto-ignition temperature (°C)

No data available.

##### Lower and upper explosion limit (% v/v)

No data available.

#### Solubility

##### Solubility in water

Completely soluble

##### n-octanol/water coefficient (LogKow)

No data available.

#### Solubility in fat (g/L)

No data available.

#### 9.2. Other information

##### Other physical and chemical parameters

No data available.

##### Oxidizing properties

No data available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Product/substance	ethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	7060 mg/kg bdw ·

Product/substance	ethanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD lo
Result:	20 gm/kg bdw ·

Product/substance	ethanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	20000 ppm/10 H ·

Product/substance	propan-2-ol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	4570 mg/kg ·

Product/substance	propan-2-ol
-------------------	-------------

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	13400 mg/kg ·

Product/substance	propan-2-ol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	30 mg/l ·

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

##### Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance	ethanol
Species:	Fish
Duration:	96 hours

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Test:	LC50
Result:	12,0 - 16,0 ml/l ·

Product/substance	ethanol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	9268 - 14221 mg/l ·

Product/substance	propan-2-ol
Species:	Fish
Duration:	48 hours
Test:	LC50
Result:	8970-9280 mg/L ·

Product/substance	propan-2-ol
Species:	Daphnia
Duration:	24 hours
Test:	EC50
Result:	9714 mg/L ·

Based on available data, the classification criteria are not met.

#### 12.2. Persistence and degradability

Product/substance	ethanol
Conclusion:	-

#### 12.3. Bioaccumulative potential

Product/substance	ethanol
Conclusion:	-

Product/substance	propan-2-ol
LogKow:	0,0500
Conclusion:	-

#### 12.4. Mobility in soil

propan-2-ol  
LogKoc = 0.117995, High mobility potential.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

#### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

#### 12.7. Other adverse effects

None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.  
HP 3 - Flammable  
Dispose of contents/container to an approved waste disposal plant.  
Waste regulation (SFS 2020:614).

#### EWC code

Not applicable.

#### Contaminated packing

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	1993	FLAMMABLE LIQUID, N.O.S. (ethanol, isopropanol)	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	Limited quantities: 1 L Tunnel restriction code: 2 (D/E) See below for additional information
IMDG	1993	FLAMMABLE LIQUID, N.O.S. (ethanol, isopropanol)	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	Limited quantities: 1 L EmS: F-E S-E See below for additional information
IATA	1993	FLAMMABLE LIQUID, N.O.S. (ethanol, isopropanol)	Transport hazard class: 3 Label: 3 Classification code: F1	II	No	See below for additional information

\* Packing group

\*\* Environmental hazards

### Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

People under the age of 18 shall not work with this product. This does not apply if the working task is:

- performed by young people who have completed upper secondary education or equivalent education for the task or
- included in teaching that is located in a school premises or other place that is specially arranged for teaching, or
- included in supervisor-led internships for young people, or
- of such a nature that the risk of injury is considered to be minimal.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

#### Biocidal Products Regulations

Product type: PT1 - Human hygiene

Restrictions on use

-

Directions for use and dose rate

-

Additional information

-

#### REACH, Annex XVII

ethanol is subject to REACH restrictions (entry 40).

propan-2-ol is subject to REACH restrictions (entry 40).

#### Additional information

Tactile warning.

#### Sources

The Swedish Work Environment Authority's regulations and general guideline (AFS 2023:2) on planning and organizing work environment work - basic obligations for you with employer responsibility

The Swedish Work Environment Authority's regulations and general guideline (AFS 2023:2) on planning and organizing work environment work - basic obligations for you with employer responsibility

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

The Swedish Civil Contingencies Agency 2015:8 regulations on measures to prevent and limit the consequences of serious chemical accidents.

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products.

Waste regulation (SFS 2020:614).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EC = Effective concentration  
ED = Effective dose  
EINECS = European Inventory of Existing Commercial chemical Substances  
EL = Effective Loading  
ErC = Concentration associated with x% growth rate response  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
HP = Hazardous Property code  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IC = X maximum inhibitory concentration  
IMDG = International Maritime Dangerous Goods  
LC = Lethal concentration  
LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans  
LD = Lethal dose  
LOAEC = Lowest Observed Adverse Effect Concentration  
LOAEL = Lowest Observed Adverse Effect Level  
LOEC = Lowest Observed Effect Concentration  
LogKow = logarithm of the n-octanol/water coefficient  
LL = Lethal Loading  
M = For multiplication factor  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
NOAEC = No Observed Adverse Effect Concentration  
NOAEL = No Observed Adverse Effect Level  
NOEC = No Observed Effect Concentration  
NOELR = No Observable Effect Loading Rate  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the mixture in regard to physical hazards has been based on experimental data.

#### The safety data sheet is validated by

mbh

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: SE-en